

Linden

- The Linden combines modern styling with robust durability. Its double UV stable polycarbonate bowl enclosed by a fully galvanised steel frame help make this a very vandal resistant fitting.
- Various optics/reflector options to reduce light pollution and skyglow, while providing a variety of distributions appropriate to most applications
- Ease of maintenance with no-tool access and ¼ turn sealed lamp holder design
- EasyFit adapter for ease of installation and accurate alignment of luminaire
- IP66 optical compartment



Technical info

Materials	Body: Spun aluminium canopy canopy, Mild steel galvanised fabricated frame Glazing: Double UV stable polycarbonate, Acrylic optional
Ingress Protection	IP66 optical compartment IP44 gear compartment
Finishes	Polyester powdercoat to any BS / RAL colours Stoving acrylic painted to any BS / RAL colours
Optics	Can accommodate our range of optics for both street and car park lighting Call for details
Gear	Upto 70W SONT Upto 150W MH Upto 90W Cosmopolis Upto 150W Ceramic Metal Halide LED Array Compact Fluorescent
Fixings	Stainless Steel
Recommended Height	4m - 6m
Mounting	Post top Outreach bracket
Mounting Details	Post top or outreach bracket Dia 78mm spigot
Maintenance	Hinged lid for access to gear and lamp. Lamp change via 1/4 turn lampholder. No tools required
Weight	Call for specific details
Photo Cell	Miniature PEC

Typical Applications

- ✓ Amenity
- ✓ Exterior
- ✓ House Builder




c a n d e l a
 L I G H T